

# FC4150Fxx Product Brief

[FC4150F512, FC4150F2M, FC41501M\_A, FC4150F1M\_B]

The FC4150F512, FC4150F2M, FC41501M\_A, and FC4150F1M\_B constitute the FC4150 family of microcontrollers with diverse memory sizes, packages, and peripherals for design scalability.

The FC4150 product series builds on the Arm® Cortex®-M4F core to deliver high-performance 32-bit computing for cost-sensitive and low-power automotive applications. The FC4150 family offers a broad range of options for you to choose from.

## Key Features

- 32-bit ARM® Cortex®-M4F core
- Up to 150 MHz execution speed
- Up to 2 MB PFlash, 256 KB DFlash, and 256 KB RAM
- Temp Grade1/-40°C to +125°C
- ISO 26262 ASIL-B support
- Package: LQFP-64, -100, -144, -176-EP
- AEC-Q100

## Target Applications

- Body Control Module (BCM)
- Door
- Seat
- Window
- Power Tail Gate (PTG)
- Ambient lighting
- On-Board Charger (OBC)
- Motor control
- P-Box
- Airbag
- Heating, Ventilation, and Air Conditioning (HVAC)
- T-Box
- Camera Monitor System (CMS)
- 48V Battery Management System (BMS)
- Thermal Management System (TMS)

# 1 Block Diagrams

The following figures show the block diagrams of the FC4150 family. For a detailed comparison, refer to [Table 1. FC4150 feature list.](#)

Figure 1. FC4150F2M block diagram




Figure 2. FC4150F1M\_A block diagram




Figure 3. FC4150F1M\_B block diagram





Figure 4. FC4150F512 block diagram



## 2 Features

The FC4150 product series has the following features:

### 2.1 Overview

- **Operating Environment**
  - Voltage range: 3.0 V to 5.5 V
  - Ambient temperature ( $T_A$ ) range: - 40°C to + 125°C; junction temperature ( $T_J$ ) range: - 40°C to + 150°C
- **Arm Cortex-M4F Core**
  - 150 MHz frequency with 2.66 Dhrystone MIPS per MHz
  - Armv7 Architecture and Thumb-2 ISA
  - Digital Signal Processing (DSP) instruction
  - Single-Precision Floating Point Unit (FPU)
  - Support Memory Protection Unit (MPU) with 8 regions
- **16-channel Direct Memory Access (DMA) with selected DMA source**
- **Clock Sources**
  - 16 ~ 48 MHz Fast Oscillator (FOSC) with up to 50 MHz DC external input clock in bypass mode
  - 32 kHz Slow Oscillator (SOSC)
  - 96 MHz Fast Internal RC Oscillator (FIRC96M)
  - 12 MHz Slow Internal RC Oscillator (SIRC12M)
  - 32 kHz Slow Internal RC Oscillator (SIRC32k)
  - Up to 200 MHz Phased Lock Loop (PLL0) with reference from FIRC48M or FOSC
- **Power Management**
  - Four power modes: RUN, WAIT, STOP and Standby. Optional 64 KB RAM retention in standby mode
- **Memory**
  - Up to 2 MB program flash memory with Error Correction Code (ECC)
  - Up to 256 KB data flash memory with ECC
  - Up to 256 KB SRAM with ECC
  - 8 KB instruction cache for Flash
  - Octal Serial Peripheral Interface (OSPI) with up to 50 MHz DDR support
  - 96 KB ROM with CM4 core self-test/Flash program & erase/ Hardware Secure Module (HSM) APIs
- **Analog**
  - Two 12-bit Successive Approximation (SAR) Analog-to-Digital Converters (ADCs) with up to 32-channel analog inputs per module
  - Up to three Analog Comparators (CMPs) with internal 8-bit Digital-to-Analog Converter (DAC)
- **Debug Functionality**
  - Serial Wire/JTAG Debug Port (SWJ-DP) combines
  - Data Watchpoint and Trace (DWT)
  - Instrumentation Trace Macrocell (ITM)
  - Embedded Trace Macrocell (ETM)
  - Trace Port Interface Unit (TPIU)
  - Flash Patch and Breakpoint (FPB) Unit
  - JTAG Test Access Port (TAP) and boundary scan support

- **Human-Machine Interface (HMI)**
  - Up to 160 GPIO pins with interrupt support
  - Non-maskable Interrupt (NMI)
  - GPIO input/output interface
- **Communications Interfaces**
  - Six FC Universal Asynchronous Receiver/Transmitter (FCUART) modules with LIN support
  - Four FC Serial Peripheral Interface (FCSPI) modules; support 1/2/4 data lines and master/slave mode
  - Two FC Inter-Integrated Circuit (FCIIC) modules
  - Up to six FLEXCAN modules with CAN FD (optional) and PNET support on FLEXCAN0-2
  - Up to one 10/100 Mbps Ethernet with IEEE1588 and AVB (For FC4150F2M only)
  - Up to two Inter-IC Sound (I2S) modules
  - Four Trigger Selects (TRGSELS) for on-chip bus connection
  - One Lookup Unit (LU) module with 4 lookup tables
- **Safety and Security**
  - Hardware Secure Module (HSM) with crypto algorithms including AES/SM4/ECC/RSA/SHA/SM3/SM2/SM9
  - CCM/GCM/ECB/CTR/CBC etc. mode
  - Support random number generation and pseudo random number generation
  - Key import/export management
  - ECC on flash and SRAM memories
  - Memory Access Protection (MAP) on system SRAM
  - Peripheral Access Protection on APB bridge (AFCEB)
  - One Cyclic Redundancy Check (CRC) module
  - Two Internal Watchdogs (WDOG) with window function
  - One FunSa Watchdog Monitor (FWM) module
  - One Interface Safety Monitor (ISM) module to monitor the critical signals delay/period/duty etc.
  - CM4 core self-test API in ROM code
- **Timers**
  - Up to eight Flexible Timer Unit (FTU) modules with IC/OC/PWM function
  - One Always-on Timer (AONTIMER) with standby wake up capability
  - Two Programmable Timers (PTIMERS)
  - One FC Programmable Interrupt Timer (FCPIT) with 4 channels
  - One Real-Time Clock (RTC)
  - Up to two 56-bit Timer Stamps (TSTMPs) with four 32-bit compare channels. The TSTMP0 runs at 1MHz divided from SIRC12M; and the TSTMP1 runs at Core clock
- **Package:** 100LQFP, 144LQFP and 176LQFP-EP package options
- **Qualification:**
  - ASIL B certified according to ISO 26262
  - AEC-Q100 Grade 1 (-40°C to 125°C)

## 2.2 Feature Comparison

The table below lists the differences in major features and peripheral counts of four chips from the FC4150 family.

**Table 1. FC4150 feature list**

Features		Chips			
		FC4150F512	FC4150F2M	FC4150F1M_A	FC4150F1M_B
Automotive cert.	Temp. Grade	Grade1/ -40°C to +125°C			
Function Safety		ASIL B			
Power Design	Voltage Range	3.0V to 5.5V			
	T <sub>A</sub>	-40°C to +125°C			
	T <sub>J</sub>	-40°C to +150°C			
CPU	Core	Cortex-M4F			
	Frequency	150 MHz			
	MPU	Yes			
	CACHE	8 KB			
	DMA Channels	16			
Memory	PFlash/Bank	512 KB/2	2 MB	1 MB	1 MB/2
	DFlash	Configurable	256 KB		128 KB
	RAM	128 KB	256 KB		128 KB
	ROM	96 KB			128 KB
Clock		Multi clocks, including FIRC96M/SIRC12M/SIRC32K/FOSC48M/SOSC32K/PLL			
Digital IOs		124	160	124	
Peripherals	System	MCM	Yes		
		AFCB	Yes		
		MAP	Yes		
		DMA	Yes		
		WKU	Yes		
		PMC	Yes		
		SMC	Yes		
		RCM	Yes		
		SEC	Yes		
		CORDIC	No		Yes
		SMISC	Yes		
	Memory	FMC	Yes		
		CCU	Yes		
		OSPI	No	Yes	
	Clocking	SCG	Yes		
		PCC	Yes		
	Function Safety	FWM	Yes		
		WDOG	2		
		EIM	Yes		

Features		Chips			
		FC4150F512	FC4150F2M	FC4150F1M_A	FC4150F1M_B
Peripherals	Function Safety	ERM	Yes		
		INTM	Yes		
		CMU	4		
		ISM	Yes		
	Security	CRC	Yes		
	HMI	GPIO	Yes		
		PORT	Yes		
		TRGSEL	4		
		LU	Yes		
	Analog	ADC	2 × 32-ch		2 × 24-ch
		CMP	3		1
	Timer	FTU	6	8	6
		FCPIT	Yes		
		TSTMP	No	1	2
		RTC	Yes		
		AONTIMER	Yes		
		PTIMER	2		
		FREQM	No		Yes
	Comm.	FCSPI	4		
		FCIIC	2		
		FCUART	6		
		FLEXCAN <sup>1</sup>	6	3	
		I2S	2	No	
ENET		No	Yes	No	
Security		HSM		HSM-Lite	
Package	64LQFP	Yes	No	Yes	
	100LQFP	Yes			
	144LQFP	Yes			
	176LQFP-EP	No	Yes	No	

1. Optional CAN FD support for FLEXCAN0/1/2.

# Revision History

Revision	Date	Changes
0.1	2023/07/14	Initial release

Flagchip



Copyright © 2023 Suzhou Flagchip Semiconductor Co., Ltd. All rights reserved.

## Contact Us

### Headquarters:

Room 213, 2nd Floor, Suite Z104, Building 2, NO.78, East Jinshan RD, New District, Suzhou, Jiangsu 215011, P.R. China

**Website:** [www.flagchip.com.cn](http://www.flagchip.com.cn)

**TEL:** +86-512-66166689

## Disclaimer

This document is the property of the Suzhou Flagchip Semiconductor Co., Ltd. (hereinafter referred to as "Flagchip"). Any information provided in this document is only for reference purposes.

Except as expressly provided herein, no part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of Flagchip. Flagchip hereby disclaims any responsibilities for any losses, expenses, claims, damages, and liabilities related to the use of the information. All information described herein is subject to change without further notice.

ARM and Cortex are registered trademarks of ARM Limited. All other trademarks mentioned in this document are the property of their respective owners.